

# Technical Data.

MODEL NO	TPRS-19		TPRS-25		TPRS-50	
Measurement	测试数据					
Frame	框架	Double	Double		Single Deck Single Side	
No of Positions	工位数	120	96		24	
Per Section	每节工位	10	8		2	
No of Section	节数	12	12		12	
Section Pitch (MM)	节距离	1830	2130		2830	
Spindle Gauge (MM)	主轴尺寸	360	525		900	
Machine Dim (Ft) LxWxH	77.2 x2.7 x 5.8		88.4x3.4x7.6		85.1 x 37x6.3	
Machine Dim (Mtr) LxWxH	机器尺寸米	23.6x0.8x1.8	27x1.1x2.3		26x1.2x1.9	
Pot Size (MM)	锭罐尺寸	100(MM)	140(MM)		200(MM)	
Denier Range	纤度范围	300-1200 D	600-3000 D		2500-12000 D	
Speed	速度	6000	4500		3500	
Connected Load	装机功率	15	48		29	
Machine Length	机器长度	24 Meter 米	27 Meter 米		26 Meter 米	
<b>Input / Feed Package / Spindle</b>						
Twist Range (TPM)	捻度范围	150-1500	150-1500		150-1500	
Feed Package (MM)	输入卷装尺寸	32x36x360	32x36x320		45x 56x290	
Feed Package Type	输入卷装形状	C 叩 s	Bottle / Cheese		Parallel Cheese	
Feed Package Max Dia (MM)	输入最大直径	100	135		200	
Feed Package Wt	卷装重量	1 Kg	1.6 Kg		4 Kg	
<b>Takeup Package 卷绕包装</b>						
Takeup Package (MM)	卷绕包装尺寸	46x57x230	46x57x290		Min ID 45 x L 290	
Takeup Package Type	卷绕包装形状	Paper Tube				
Takeup Package Max Dia	卷绕包装最大尺寸	250 MM	300 MM		400 MM	
Takeup Wt Knot Less (Gms)	卷绕无结包装重量	1.5 Kg	2.5 Kg		12 KG	
Winding Traverse	动程	200	250		250	
Ply Sensor/Cutter	并捻传感器/切丝器	Yes	Yes		Yes	
<b>Spindle Driving 主轴驱动</b>						
Take-Up Drive	卷绕驱动	Common	Common		Individual	
Spindle Drive	主轴驱动	Tangential	Individual		Individual	

TPRS-19	宽度	高度	工位数							
Position	Width	Height	Position	50	60	80	90	100	110	120
Length(MM)	长度	800	Length	10700	12530	16190	18020	19850	21680	23510

TPRS-25	宽度	高度	工位数							
Position	Width	Height	Position	24	32	40	48	64	72	80
Length(MM)	1010	2300	Length	7770	9900	7770	14160	18420	20550	22680

TPRS-50	宽度	高度	工位数							
Position	Width	Height	Position	8	10	12	14	16	20	24
Length(MM)	1120	1900	Length	7700	9500	11300	13100	14900	18500	22100